


Customers



SHINWOOSHIN

Steady
World-best
Solution




Automotive parts with innovation and smart factory



936-1, Gyeongcheong-ro, Namcheon-myeon, Gyeongsan-si, Gyeongsangbuk-do, Republic of Korea
Tel 82-53-811-5880 Fax 82-53-811-5881 Website : www.sws88.com E-mail : sws88@sws88.com





MESSAGE

ShinWooShin Co. has been running for the hopeful future based on the technological skills and the challenge spirit that has been developed since its foundation in 2001

We promise to be a leading company that will lead the future with continuous R&D and innovation by maintaining dynamism and trust by maintaining a partnership with all of our employees while realizing customer satisfaction with the best quality in preparation for the ever changing environment of the company.


Name	ShinWooShin Co., Ltd.	Sales	KRW 15Billion ('18)
President & CEO	Ji-Woo Lee	Credit Ratings	BBB ('17)
Establishment	2001. 9. 25	Total Workforce	63 employees
Business Type	Automobile Patrt (Clamp Band, Press, etc.)	Customer	HYUNDAI WIA, PYUNG HWA, etc.

MANAGEMENT PHILOSOPHY



In order to meet the needs and wants of customers in a timely manner, Based on management philosophy, ShinWooShin Co., We are doing 『S.W.S』 mission as followings.




POWER TRAIN & DRIVE LINE PRESS PARTS



TRANSMISSION & ETC.



C.V.JOINT PART



CLAMP BAND



Step-less EAR Clamp

Open Dia.	Thick.	Width	Ear Width Inside	Material
Ø27.0 ~ Ø531.1	0.8 ~ 1.0	10	10	SUS304

- High Crimping Force & Assembly Efficiency
- Improved Locking Strength
- Various kinds of type(patent free)



LOW PROFILE Clamp

Close Dia.	Thick.	Width	Material
Ø27 ~ Ø101.0	0.6 ~ 0.8	7 ~ 10	SUS301 or 304

- High Crimping Force & Low Assembled Height
- Enhanced Reliability
- Securing own patent



High Tensile HOOK Clamp

Close Dia.	Thick.	Width	Material
Ø71.1 ~ Ø101.6	0.7	10	SUS301 or 304

- Compact & Reusable Type
- Assembled by Pneumatic Pincer



HOOK Clamp

Close Dia.	Thick.	Width	Material
Ø27.0 ~ Ø100.8	0.4 ~ 0.5	7	SUS301 or 304

- Compact & Economic Size
- Assembled by Pneumatic Pincer